



Quick Start

impulse 200E Network Encoder and Streamer



Congratulations on the purchase of Impulse 200E. Follow these installation and configuration instructions to get started. The Web interface will provide users with a simple and intuitive way to start streaming quickly. If you need assistance, please contact Sencore procure at procare@sencore.com or visit www.sencore.com.

1 Content

Unpack the box and verify all contained items are present:

- Impulse-200E
- Power adaptor



If any of these items is missing or damaged, please contact Sencore to obtain replacement.

2 Installation

1. Connect appropriate I/O cables (HDMI/SDI and CC/MIC) to correct ports on the back of the unit. Insert an SD card or USB disk if you plan to use the recording or playback feature.
2. Connect an Ethernet cable from your network to the RJ45 port on the unit.
3. Connect the power adaptor and see booting up status on the front panel.

3 Management




The Impulse 200E can be managed through its web interface or the keypad and the LCD screen on the front panel.

- To use the Web-GUI for management :

Connect an Ethernet cable from your network to the Impulse 200E. Keep in mind that the default address of the Impulse 200E may need to be changed to be within the same subnet as your network. Open a web browser (IE7 or above, Firefox 3.5 or above, or Chrome) and type in <http://192.168.1.100>. Default account and password are **admin/admin**.

- To use front panel for management

Follow these instructions to navigate the and configure available features:

1. Press  to enter the menu and confirm or save the configuration.
2. Press  to return to the previous menu.
3. Press  to move the cursor on the screen.

